




~DIN 8140 A

AMECOIL®

SR



BN 910

Filetti riportati

INOX A2

 [3D Cadenas](#)



1. Forare
2. Maschiare il foro
3. Montare con l'attrezzo classico
4. Montare con il mandrino
5. Troncare il perno di presa

L = lunghezza nominale nello stato non montato circa 1/3 più corta

Article#	d ₁	d ₂	Ø preforo	L
1808680	M3	3,8-4	3,2	3 / (1d)
1808699				4,5 / (1,5d)
1811886				6 / (2d)
1811894	M4	5,15-5,35	4,2	4 / (1d)
1371991				6 / (1,5d)
1811908				8 / (2d)
1372009	M5	6,35-6,6	5,2	5 / (1d)
1372017				7,5 / (1,5d)
1372025				10 / (2d)
1372033	M6	7,6-7,85	6,3	6 / (1d)
1372041				9 / (1,5d)
1372068				12 / (2d)
9036143				15 / (2,5d)
1372076	M8	9,85-10,1	8,4	8 / (1d)
1372084				12 / (1,5d)
1372092				16 / (2d)
8152942				20 / (2,5d)
1372106	M8x1	9,85-10,1	8,3	12 / (1,5d)
1372114	M10	12,1-12,5	10,5	10 / (1d)
1372130				15 / (1,5d)
1124854				20 / (2d)

L = lunghezza nominale nello stato non montato circa 1/3 più corta

Article#	d ₁	d ₂	Ø preforo	L
1376772	M10x1,25	12,1-12,5	10,4	15 / (1,5d)
1376780	M12	14,4-14,8	12,5	12 / (1d)
1376799				18 / (1,5d)
1376802				24 / (2d)
1376810	M12x1,25	14,4-14,8	12,4	18 / (1,5d)
1376829	M14	16,8-17,7	14,5	21 / (1,5d)
1376837	M16	19-19,9	16,5	16 / (1d)
1376845				24 / (1,5d)
1376853				32 / (2d)
1376861	M16x1,5	19-19,9	16,5	24 / (1,5d)
9036144	M20	23,7-24,2	20,75	20 / (1d)