Composite objects: `structs` and `classes`

P. Ronchese
Dipartimento di Fisica e Astronomia “G.Galilei”

Università di Padova

“Object oriented programming and C++” course

Composite objects

C/C++ allow the definition of “composite objects”, i.e. objects containing several variables and/or other objects

- Useful to group together related variables/object
- Two types of composite objects: `struct` and `class` :
  - `struct` comes from plain-C
  - `class` is C++-specific

```
struct Point {
  float x;
  float y;
}; // a semicolon is required
```

Basic properties

Basic properties of composite objects

- their pointer or reference can be taken and passed or returned by a function
- they can contain native variables and/or their pointers
- they can contain other composite objects and/or their pointers
- they can contain pointers to themselves (directly or indirectly)
- they cannot contain instances of themselves
- their “members” can be accessed
- other properties (C++ specific, not available in plain C) will be shown later

Declaration and definition of `struct`s

In C/C++ all variables must be “declared” before being used; `struct`s need also being “defined”

Declaration: a name is simply stated as identifying a `struct`.
It can be repeated.

```
// Point declaration
struct Point;
Point* pp;
```

Definition: all the members of the `struct` must be specified.
Only one definition can exist in one translation unit.
A definition is also a declaration.

```
// Point definition
struct Point {
  float x;
  float y;
};
Point p;
```

- To create a `struct` the definition is necessary
- To create a pointer the declaration is enough

Access to members

When a `struct` has been created, its member are accessed with their names

```
Point p;
p.x=-2.35;
p.y= 6.71;
```

The memebers of a `struct` can be accessed starting from a pointer, too

```
Point p;
Point* pp=&p;
(*pp).x=4.59; // parentheses are needed
pp->y=-12.86; // equivalent to(*pp).y=-12.86
```

Memory sharing: `union`s

In a `struct` the members are stored in memory sequentially; in an `union` the members share the same memory locations.

All the objects are stored starting from the same memory location

```
union Misc {
  float x;
  int i;
  char* p;
};
Misc m;
```

- The size of the `union` is the size of the largest object
- Only one object can be stored at once
- Undefined results are obtained when writing one object (e.g. `m.x`) and reading another one (e.g. `m.i`)

`struct`s and `class`es

`class`: the main improvement of C++ versus plain C

A `class` is essentially an evolution of a `struct`

Plain-C `struct`s contain only variables or other objects,
C++ `class`es provide several new functionalities:

- constructor(s) and destructor,
- functions handling data members,
- access specifiers to control access to data.

`class` “interface”

The definition of a `class`, with all its functions, is also called “interface”

```
class Point {
 public:  // accessible by all functions
  Point(float x, float y); // constructor
  ~Point();                //  destructor
  float getX() const; // member functions
  float getY() const;
  float dist(const Point& p) const;
 private: // accessible only by the class
  float xp; // member data
  float yp;
};
```

The standard extended to `struct`s the properties of `class`es

Constructor and destructor

The “constructor” and “destructor” of a class are executed when an object is created or destroyed

```
Point::Point(float xi, float yi):
 xp(xi),
 yp(yi) {
}
Point::~Point() {
}
```

- Data members are initialized in the order they’re declared in the class definition, not as they’re listed in the constructor.
- Destructor is often empty; typical operations are:
  - `delete` dynamic objects used by the class
  - close files opened and used by the object
  - free other resources allocated by the object

Function members

Function members (sometimes called "methods") have direct access to member data of the object

```
float Point::getX() const {
  return xp;
}
float Point::getY() const {
  return yp;
}
float Point::dist(const Point& p) const {
  return sqrt(pow(xp-p.xp,2)+pow(yp-p.yp,2));
}
```

Functions are declared `const` when
they do not modify any member of the object;
only `const` function can be called for `const` objects.

Default constructor and destructor

If the definitions of a class does not contain any constructor and/or destructor, “default” ones are automatically provided

- Default constructor (with no arguments): the default constructor for each member is called
- Default destructor: the destructor for each member is called
- Default copy and assignment: each member is simply copied

Copy constructor

The copy constructor takes one single argument, of the same class. It’s used any time an object is copied:

- When an object is passed to a function by value
- When an object is returned by a function

Declaration, definition and implementation of `class`es

- A `struct`/`class` declaration can appear any number of times
- A `struct`/`class` definition (also called “interface”) must appear once and only once in each translation unit using it
- A `struct`/`class` implementation (functions code) must appear once and only once in the whole program (function implementation can anyway be inlined in the definition)

`class` definitions are usually coded in “header files”, with “header guards” to prevent multiple inclusions

```
#ifndef Point_h
#define Point_h
class Point {
  ...
};
#endif
```

Cross references among `class`es

Two (or more) `class`es may exist, each one using the other as argument of it own functions: both must know about the other

```
class Line;
class Point {
  ...
   float dist(const Line& l) const;
  ...
};
```

```
class Point;
class Line {
  ...
   float dist(const Point& p) const;
  ...
};
```

`friend` functions and `class`es

A `class` can declare `friend` functions and `class`es, allowed to access it `private` members (use sparingly!).

```
class Point {
  friend class Line;
  // all functions of "Line" can access
  // private members of "Point"
  ...
};
class Line {
  friend
  float Point::dist(const Point& p) const;
  // only the function "dist" of "Point"
  // can access private members of "Line"
  ...
};
```

Self reference

Each instance can obtain the pointer to itself from `this`

- It can be used as parameter when calling functions
- It can be returned by member functions
- It can be dereferenced to obtain the object instance

```
float Line::dist(const Point& p) const {
  return fabs((a*p.getX())+(b*p.getY())+c)/
         sqrt((a*a       )+(b*b       )  );
};
```

```
float Point::dist(const Line& l) const {
  return l.dist(*this);
};
```

Shared members declaration

Each “instance” of a `class` contains its own members, e.g. each `Point` contains its `x` and `y`

A member shared by all the instances of a class can be declared by using the keyword `static`

```
class Line { // ax+by+c=0
 public:
  Line(const Point& p1,const Point& p2);
  ~Line();
  Point intersect(const Line& l) const;
 private:
  static float tolerance;
  float a;
  float b;
  float c;
};
```

Shared members initialization

Shared (`static`) data members are not bound to any specific instance of a class

- They are created at the execution start, even if no instance is created in the execution (but for dynamic libraries)
- They must be initialized, only once, outside any function

```
float Line::tolerance=1.0e-05;
Point Line::intersect(const Line& l) const {
  float det=(a*l.b)-(b*l.a);
  float chk=pow(  a,2)+pow(  b,2)+
            pow(l.a,2)+pow(l.b,2);
  if(fabs(det/chk)<tolerance)
     return Point(FLT_MAX,FLT_MAX);
  return Point(((b*l.c)-(c*l.b))/det,
               ((c*l.a)-(a*l.c))/det);
}
```

Operator members

Not only functions but also operators can be defined for classes

```
class Vector2D {
 public:
  Vector2D(float x, float y);
  ~Vector2D();
  float getX() const;
  float getY() const;
  Vector2D  operator+(const Vector2D& v);
  Vector2D& operator*=(float f);
 private:
  float xv;
  float yv;
};
```

- Operators are defined as other functions.
- Assigment operators return a "`*this`".

Operators definition

Operator members are to be defined as member functions

```
Vector2D  Vector2D::operator+(const
                                Vector2D& v) {
  return Vector2D(xv+v.xv,yv+v.yv);
}
Vector2D& Vector2D::operator*=(float f) {
  xv*=f;
  yv*=f;
  return *this;
};
```

Class operators can be used as the built-in ones, or through explicit function calls

```
Vector2D u( 2.3,4.5);
Vector2D v(-1.6,6.9);
Vector2D s=u+v;
u*=3; // equivalent to u.operator*=(3)
```

Operator functions

Operators can be defined also as global functions, where at least an argument must be a `class`

```
Vector2D operator+(const Vector2D& vl,
                   const Vector2D& vr) {
  return Vector2D(vl.getX()+vr.getX(),
                  vl.getY()+vr.getY());
}
Vector2D& operator*=(Vector2D& v,float f) {
  v = Vector2D(v.getX()*f,v.getY()*f);
  return v;
}
```

- Both implementations can be present
- The compiler flags as an error any ambiguous call
  - `u.operator+(v)` calls the operator member
  - `operator+(u,v)` calls the operator function

Functors

Objects usable as functions are called “functors”.

```
class Func {
 public:
  Func(int n):f(n) {};
  float  operator()(float x) {return f*x;}
 private:
  int f;
};
int main() {
  // create a Funct setting it at 3
  Func m(3);
  // call the Funct with 5
  cout << m(5) << endl;
  return 0;
}
```

I/O Operators

Operator functions can be defined to write/read objects

```
std::ostream& operator<<(std::ostream& os,
                         const Vector2D& v) {
  os << v.getX() << " " << v.getY();
  return os;
};
std::istream& operator>>(std::istream& is,
                         Vector2D& v) {
  float x,y;
  is >> x >> y;
  v=Vector2D(x,y);
  return is;
};
```

I/O operator functions take
a `std::istream&` or `std::ostream&` as argument,
and return the same at the end

Nested classes

A class can be defined inside the definition of another one (being visible outside or not if it's public or private respectively)

```
class Outer {
 public:
  ...
  class InnerPub {
    ...
  };
 private:
  class InnerPri {
    ...
  };
  ...
};
```

A public nested class can be accessed by using the scope resolution operator ::
Outer::InnerPub.
Examples will be shown in the following.

Having several classes nested inside the same enclosing one emphasizes the relations among them.

Name conflicts

Names of `class`es must be unique throughout the whole program (libraries included): conflicts could arise.

Functions and `class`es can be declared and defined inside “namespaces”

```
namespace Geom {
  class Line;
  class Point {
  ...
  };
};
```

Classes defined inside namespaces can be accessed by mean of the “scope” operator `::`

```
...
int main() {
  Geom::Point p(1.2,7.4);
  ...
  return 0;
};
```

Default namespaces

Adding namespace to a `class` name produces a long name...

- A `typedef` can be used
- An `using` declaration or directive can be added

```
typedef Geom::Point point;
// define "point" as a short name
```

```
using Geom::Point;
// Makes "Point"
// visible out of namespace "Geom"
```

```
using namespace Geom;
// Makes all names in "Geom"
// visible outside
```

An `using` declaration or directive affects
all the following code in the same translation unit:
avoid including "`using`" directives in header files

Error handling

A lot of situations may occur where an operation cannot be performed:

- a division by zero is required,
- the square root of a negative number is required,
- an unvalid pointer is to be dereferenced,
- ...

An error flag is to be set, propagated back and properly handled (unless there's some reason to prefer an execution crash)

Exceptions are objects that:

- are "thrown" where the error condition occur
- are "catched" anywhere in the function calling sequence
- contain informations about the error

Exception objects

Any object can be (in principle) used as exception

```
class MathException {
 public:
  enum errorType {divByZero,sqrNeg};
  MathException(errorType e) {error=e;}
  ~MathException() {}
  errorType get() const {return error;}
 private:
  errorType error;
};
```

```
float x;
int i;
...
if(i==0)throw
   MathException(MathException::divByZero);
x/=i;
```

Exception catching

Exceptions are handled by mean of “`try`” and “`catch`” blocks

```
try {
   ...  // any code that could possibly
   ...  // throw a "MathException"
}
catch (MathException e) {
   if(e.get()==MathException::divByZero)
       cout << "division by zero" << endl;
};
```

When an exception is thrown
all the calling functions are immediately terminated
going back until a “`catch`” clause is found.