Function and `class` templates

P. Ronchese
Dipartimento di Fisica e Astronomia “G.Galilei”

Università di Padova

“Object oriented programming and C++” course

Similar operations

Similar operations can be defined for different types

All the following can be defined for all kind of numbers, `int` , `float` and so on:

- basic operations `+` , `-` , `*` , `/`
- absolute value
- power
- ...

More complex objects could share more complex operations

Generic types

C++ allows writing code with “generic” object types,
performing the same operations
with objects having different types

A lot of code replication can be avoided

- Work economy in code writing
- Ease of maintenance
- Error reduction

Function templates declaration and definition

A function can take arguments of generic type by declaring it a "function template"

```
template<class T>
void perm(T& x,T& y,T& z) {
  // make a cyclic permutation of x,y,z
  T t = x;
  x = y;
  y = z;
  z = t;
  return;
}
```

The compiler takes care of calling the proper instance

- any number of template arguments with any name can be used
- `template<typename T>` can be used as well

Template functions usage

The full definition must come before the usage:
a simple declaration is not sufficient

```
template<class T>
void perm(T& x,T& y,T& z) {
   ...
}
int main() {
   int i;
   int j;
   int k;
   ...
   perm(i,j,k);
   ...
}
```

Class templates declaration and definition

Most flexibility is achieved by the use of `class` templates

A previously seen example ("`FloatArray`") can be easily used for other types than `float` by making it a `class` template.

```
template<class T> // T replaces "float"
class Array {     // everywhere
 public:          // in the class definition
  Array(int n);
  Array(const Array<T>& a);
  ~Array();
  ...
 private:
  int eltn;
  T* cont;
  void copy(const Array<T>& a);
};
```

Class templates implementation

The specification `template<class T>` must be included in the implementation of constructor(s), destructor, functions and operators

```
template<class T>
Array<T>::Array(int n):
 eltn(n),
 cont(new T[eltn]) {
}
template<class T>
Array<T>::~Array() {
  delete[] cont;
}
...
```

The implementation must come before the `class` is used: it's usually coded in "implementation files" (`.hpp`) included at the end of the header

Template `class` usage

In the declaration of objects with template type, the template parameter(s) must be specified

The usage is then exactly the same

```
#include "Array.h"
int main() {
  int i;
  int n=5;
  Array<float> a(n);
  for(i=0;i<n;++i)a[i]=i*3.2;
  for(i=0;i<n;++i)cout << i << " "
                       << a[i] << endl;
  return 0;
}
```

Type consistency

The consistency of a code template with the actually used types is performed only when an instance of the template is created

```
template<class T>
void perm(T& x,T& y,T& z) {
  cout << x.size() << " "
       << y.size() << " "
       << z.size() << endl;
  // make a cyclic permutation of x,y,z
  T t = x;
  x = y;
  y = z;
  z = t;
  return;
}
```

Works only if `T` has a function `size()` .

Nested `class` templates

A `class` template could contain a nested `class`, being referred from outside the enclosing `class` .

The compiler could be unable to know if a member of a `class` template is a type or an object: it assumes it's an object, unless a `typename` is specified.

```
template <class T> class A {
 public:
  class C {
  };
};
template <class T> class B {
 public:
  void f(A<T>* p) {
  typename A<T>::C* c; // pointer to "A<T>::C"
};
```

typename specification

```
template <class T> class A;
template <class T> class B {
 public:
  void f(A<T>* p) {
  // by default A<T>::C is an object
  // and A<T>::C * c is a multiplication
  typename A<T>::C * c;
  // adding a "typename"
  // A<T>::C is declared being a type
};
```

A typename specification is required in a declaration if:

- there's a template parameter
- there's a scope resolution operator ::

"typename" can be used in place of "class" in template declarations: template <typename T> class A

Non-type template arguments declaration

Template arguments can be not only types, but also integers, or anything similar to an `int` (`char` , `enum` ...)

Example: a fixed-size array

```
template<class T, unsigned int N>
class FixedSizeArray {
 public:
  FixedSizeArray();
  FixedSizeArray(
   const FixedSizeArray<T,N>& a);
  ~FixedSizeArray();
  ...
 private:
  T* cont;
  void copy(const FixedSizeArray<T,N>& a);
};
```

Non-type template arguments implementation

```
template<class T, unsigned int N>
FixedSizeArray<T,N>::FixedSizeArray():
 cont(new T[N]) {
};
template<class T, unsigned int N>
FixedSizeArray<T,N>::copy(
                const FixedSizeArray<T,N>& a) {
  if(cont==a.cont)return;
  delete[] cont;
  cont=new T[N];
  T* pr=a.cont+N;
  T* pl=  cont+N;
  while(pl>cont) *--pl=*--pr;
  return;
};
```

Template specialization

Function and `class` templates allow the automatic replication of the same code with different types (or integer quantities), but some special situation could require a special handling

Template specialization: the implementation of a template `class` (or one of its functions) for a specific type is provided in addition to the generic one

```
template<>
Array<int>::Array(int n):
 eltn(n),
 cont(new int[eltn]) {
  cout << "create an Array of int" << endl;
}
```

A (possibly empty) `template` specification is needed all the same