

Composite objects: `structs` and `classes`

P. Ronchese

Dipartimento di Fisica e Astronomia “G.Galilei”

Università di Padova

“Object oriented programming and C++” course

Declaration and definition of `structs`

In C/C++ all variables must be “declared” before being used;
`structs` need also being “defined”

Declaration: a name is simply stated as identifying a `struct`.
 It can be repeated.

```
// Point declaration
struct Point;
Point* pp;
```

Definition: all the members of the `struct` must be specified.
One and only one definition must exist **in each translation unit** using it.
 A definition is also a declaration.

```
// Point definition
struct Point {
    float x;
    float y;
};
Point p;
```

- To create a `struct` the definition is necessary
- To create a pointer the declaration is enough

Access to members

structs can be initialized with a list.

When a struct has been created,
its member are accessed with their names.

```
Point p={2.35,6.71};  
std::cout << p.x << " " << p.y << std::endl;
```

The members of a struct can be accessed
starting from a pointer, too

```
Point p;  
Point* pp=&p;  
(*pp).x=4.59; // parentheses are needed  
pp->y=-12.86; // equivalent to(*pp).y=-12.86
```


Memory sharing: unions

In a `struct` the members are stored in memory sequentially;
in an `union` the members share the same memory locations.

All the objects are stored
starting from the same
memory location

```
union Misc {  
    float x;  
    int i;  
    char* p;  
};  
Misc m;
```

- The size of the `union` is the size of the largest object
- Only one object can be stored at once
- Undefined results are obtained when writing one object (e.g. `m.x`) and reading another one (e.g. `m.i`)

class “interface”

The definition of a `class`, with all its functions, is also called “interface”

```
class Point {
public: // accessible by all functions
    Point(float x, float y); // constructor
    ~Point(); // destructor
    float getX() const; // member functions
    float getY() const;
    float dist(const Point& p) const;
private: // accessible only by the class
    float xp; // member data
    float yp;
};
```

- `struct` : members are `public` by default
- `class` : members are `private` by default

Declaration, definition and implementation of `classes`

- A `struct/class` **declaration** can appear **any number of times**
- A `struct/class` **definition** (also called “interface”) must appear **once and only once in each translation unit** using it
- A `struct/class` **implementation** (functions code) must appear **once and only once in the whole program**; functions can be implemented in the definition being implicitly `inline`

`class` definitions are usually coded in “header files”, with “include guards” to prevent multiple inclusions

```
#ifndef Point_h
#define Point_h
class Point {
    ...
};
#endif
```


Constructor and destructor

The “constructor” and “destructor” of a class are executed when an object is created or destroyed

```
Point::Point(float x, float y):
    xp(x),
    yp(y) {
}
Point::~~Point() {
}
```

- Data members are **initialized** in the order **they're declared** in the class definition, **not as they're listed** in the constructor: important when a member is initialized using another one.
- Destructor is often empty; typical operations are:
 - `delete` dynamic objects used by the class
 - close files opened and used by the object
 - free other resources allocated by the object

Object destruction

An object can be destroyed in different circumstances

- An automatic object is destroyed when it goes out of scope,
- A `static` object is destroyed at the execution end,
- A dynamic object is destroyed when a `delete` instruction is executed.

If an object is created with `new`
and it is not destroyed with `delete`
the destructor is NOT run.

Any resource allocated by the object is simply released
by the operating system at the execution end.

const and mutable members

Members declared `const`

- they cannot be modified during the object life
- they must be initialized in the constructor

Members declared `mutable`

- they can be modified also by functions declared `const` or through pointers to `const`
- they're to be used for members not affecting the “externally visible state” of an object.

Member initialization at declaration

C++11 only

Class members can be initialized in the definition.

```
class Pippo {
public:
    Pippo();
    Pippo(int i);
    ~Pippo();

    ...
private:
    int x = 1;
};
Pippo() { // x=1
}
Pippo(int i): x(i) { // x=i
}
```

Constructor types

Default constructor

The default constructor allows the creation of an object with no arguments:

- declared with no arguments
- declared with arguments all having a default value

Copy constructor

The copy constructor takes one single argument, of the same class. It's used any time an object is copied, e.g.:

- when an object is passed to a function by value
- when an object is returned by a function

User-defined constructor:
any constructor declared by the user
(including default and copy)

Defaulted constructor and destructor

Implicit declaration

If the definitions of a class does not contain any constructor and/or destructor, “defaulted” (i.e. implicitly declared) ones are automatically provided by the compiler itself.

- Implicitly-declared default constructor:
the default constructor for each member is called
- Implicitly-declared destructor:
the destructor for each member is called
- Implicitly-declared copy and assignment:
each member is simply copied

If any user-defined constructor is declared, with or without parameters, there's no default constructor implicit declaration.

Defaulted constructor and destructor recovery or drop

C++11 only

Defaulted constructor and destructor can be explicitly declared or removed.

```
class Point {
public:
    Point() = default; // allow d.c.
    Point(float x, float y);
    ...
};
class Line {
public:
    Line() = delete; // remove d.c.
    Line(const Point& p1, const Point& p2);
    ...
};
```

Implicitly declared members summary

A **default constructor** is **implicitly declared** if:

- no user-defined (**generic**) **constructor** is declared
- OR it's declared with the specification = `default` .

A **default constructor** is **NOT implicitly declared** if:

- at least one user-defined constructor is declared
- OR it's declared with the specification = `delete` .

A **copy constructor** is **implicitly declared** if:

- no user-defined **copy constructor** is declared
- OR it's declared with the specification = `default` .

A **copy constructor** is **NOT implicitly declared** if:

- an user-defined one is declared and implemented
- OR it's declared with the specification = `delete` .

A copy constructor (user-defined or implicitly declared)
is always present, unless explicitly `deleted`.

Delegated constructor

C++11 only

A constructor can delegate to another one.

```
class Point {
public:
    Point(float d);
    Point(float x, float y);
    ...
};
Point::Point(float d):
    Point(d,d) { // delegate to other constructor
}
```

Shared members declaration

Each “instance” of a `class` contains its own members, e.g.
each `Point` contains its `x` and `y`

A member shared by all the instances of a class can be declared by using the keyword `static`

```
class Line { // ax+by+c=0
public:
    Line(const Point& p1, const Point& p2);
    ~Line();
    Point intersect(const Line& l) const;
private:
    static float tolerance;
    float a;
    float b;
    float c;
};
```

Shared members initialization

Shared (`static`) data members are not bound to any specific instance of a class

- They are created at the execution start (or when loading dynamic libraries), even if no instance is created
- They must be initialized, only once, outside any function

```
float Line::tolerance=1.0e-05;
Point Line::intersect(const Line& l) const {
    float det=(a*l.b)-(b*l.a);
    float chk=pow( a,2)+pow( b,2)+
              pow(l.a,2)+pow(l.b,2);
    if(fabs(det/chk)<tolerance)
        return Point(FLT_MAX,FLT_MAX);
    return Point(((b*l.c)-(c*l.b))/det,
                ((c*l.a)-(a*l.c))/det);
}
```

Shared members functions

Shared (`static`) member functions, not bound to any specific instance of a class, can be declared as well

- They can be called using the “scope resolution” (`::`) operator
- They can access only `static` data members
- They cannot access `non-static` data members, but for specific objects they may have access to (e.g. passed as parameters, or global objects)

```
class Pippo {
public:
    static int count();
    ...
};
...
int j=Pippo::count();
```

Cross references among classes

Two (or more) classes may exist, each one using the other as argument of its own functions: both must know about the other

```
class Line;
class Point {
    ...
    float dist(const Line& l) const;
    ...
};
```

```
class Point;
class Line {
    ...
    float dist(const Point& p) const;
    ...
};
```

Self reference

Each instance can obtain the pointer to itself from `this`

- It can be used as parameter when calling functions
- It can be returned by member functions
- It can be dereferenced to obtain the object instance

```
float Line::dist(const Point& p) const {  
    return fabs((a*p.getX())+(b*p.getY()+c)/  
               sqrt((a*a)+(b*b)));  
};
```

```
float Point::dist(const Line& l) const {  
    return l.dist(*this);  
};
```

friend functions and classes

A class can declare friend functions and classes, allowed to access its private members (use sparingly!).

```
class Point {
    friend class Line;
    // all functions of "Line" can access
    // private members of "Point"
    ...
};
class Line {
    friend
    float Point::dist(const Point& p) const;
    // only the function "dist" of "Point"
    // can access private members of "Line"
    ...
};
```

Operator members

Not only functions but also operators can be defined for classes

```
class Vector2D {
public:
    Vector2D(float x, float y);
    ~Vector2D();
    float getX() const;
    float getY() const;
    Vector2D operator+(const Vector2D& v);
    Vector2D& operator*=(float f);
private:
    float xv;
    float yv;
};
```

- Operators are defined as other functions.
- Assignment operators return a “*this”.

Operators definition

Operator members are to be defined as member functions

```
Vector2D Vector2D::operator+(const
                               Vector2D& v) {
    return Vector2D(xv+v.xv, yv+v.yv);
}
Vector2D& Vector2D::operator*=(float f) {
    xv*=f;
    yv*=f;
    return *this;
};
```

Class operators can be used as the built-in ones,
or through explicit function calls

```
Vector2D u( 2.3, 4.5);
Vector2D v(-1.6, 6.9);
Vector2D s=u+v;
u*=3; // equivalent to u.operator*=(3)
```

Operator functions

Operators can be defined also as global functions, where at least an argument must be a `class`

```
Vector2D operator+(const Vector2D& vl,
                  const Vector2D& vr) {
    return Vector2D(vl.getX()+vr.getX(),
                  vl.getY()+vr.getY());
}
Vector2D& operator*=(Vector2D& v, float f) {
    v = Vector2D(v.getX()*f, v.getY()*f);
    return v;
}
```

- Both implementations can be present
- The compiler flags as an error any ambiguous call
 - `u.operator+(v)` calls the operator member
 - `operator+(u, v)` calls the operator function

Functors

Objects usable as functions are called “functors”.

```
class Func {
public:
    Func(int n):f(n) {};
    float operator()(float x) {return f*x;}
private:
    int f;
};
int main() {
    // create a Funct setting it at 3
    Func m(3);
    // call the Funct with 5.3
    cout << m(5.3) << endl;
    return 0;
}
```

I/O Operators

Operator functions can be defined to write/read objects

```
std::ostream& operator<<(std::ostream& os,
                        const Vector2D& v) {
    os << v.getX() << " " << v.getY();
    return os;
};

std::istream& operator>>(std::istream& is,
                        Vector2D& v) {

    float x,y;
    is >> x >> y;
    v=Vector2D(x,y);
    return is;
};
```

I/O operator functions take

a `std::istream&` or `std::ostream&` as argument,
and return the same at the end

Operators limitations

Operators must be defined and implemented as global function when:

- The left operand has built-in type (e.g. `int`, `float`, ...)
- The left operand type is a non modifiable `class` (e.g. `istream`)

Only existing operators (e.g. `+`, `-`, `*`, `/`, `=`, ...) can be redefined `classes`, no new ones can be created (e.g. `**` for exponentiation)

Nested classes

A class can be defined inside the definition of another one
(being visible outside or not
if it's `public` or `private` respectively)

```
class Outer {
public:
    ...
    class InnerPub {
        ...
    };
private:
    class InnerPri {
        ...
    };
    ...
};
```

A public nested class can be accessed by using the scope resolution operator `::`

`Outer::InnerPub`.

Examples will be shown in the following.

Having several classes nested inside the same enclosing one emphasizes the relations among them.

Type conversions by operator

Implicit type conversions

Conversion to other types can be defined with operators.

```
class Pippo {
public:
    operator int();
};
void f(int i);
```

```
...
Pippo p;
f(p);
...
```

C++11 only

An explicit operator prevents implicit type conversions.

```
class Pluto {
public:
    explicit
    operator int();
};
```

```
...
Pluto p;
f(static_cast<int>(p));
...
```

Name conflicts

Names of `classes` must be unique throughout the whole program (libraries included): conflicts could arise.

Functions
and `classes` can be
declared and defined
inside “namespaces”

Classes defined inside
namespaces can be
accessed by mean of
the “scope” operator `::`

```
namespace Geom {
    class Line;
    class Point {
        ...
    };
};
```

```
...
int main() {
    Geom::Point p(1.2, 7.4);
    ...
    return 0;
};
```

Default namespaces

Adding namespace to a `class` name produces a long name...

- A `typedef` can be used
- An `using` declaration or directive can be added

```
typedef Geom::Point point;  
// define "point" as a short name
```

```
using Geom::Point;  
// declaration: makes "Point"  
// visible without namespace resolution
```

```
using namespace Geom;  
// directive: makes all names in "Geom"  
// visible without namespace resolution
```

An `using` declaration or directive affects all the following code in the same translation unit:
avoid including “`using`” directives in header files

Exception objects

Any object can be (in principle) used as exception

```
class MathException {
public:
    enum errorType {divByZero, sqrNeg};
    MathException(errorType e) {error=e;}
    ~MathException() {}
    errorType get() const {return error;}
private:
    errorType error;
};
```

```
float x;
int i;
...
if(i==0) throw
    MathException(MathException::divByZero);
x/=i;
```

Exception catching

Exceptions are handled by mean of “try” and “catch” blocks

```
try {
    ... // any code that could possibly
    ... // throw a "MathException"
}
catch (MathException& e) {
    if(e.get() == MathException::divByZero)
        cout << "division by zero" << endl;
}
```

When an exception is thrown
all the calling functions are immediately terminated
going back until a “catch” clause is found.

Several “catch” blocks can exist,
handling exceptions of different type.

